

# Package: receptiviti (via r-universe)

September 15, 2024

**Type** Package

**Title** Text Analysis Through the 'Receptiviti' API

**Version** 0.1.9

**Description** Send text to the <<https://www.receptiviti.com>> API to be scored by all available frameworks.

**License** MIT + file LICENSE

**Imports** curl, jsonlite, digest, progressr, stringi

**Suggests** testthat (>= 3.0.0), knitr, rmarkdown, future, arrow (>= 9.0.0), dplyr, future.apply

**Config/testthat/edition** 3

**RoxygenNote** 7.3.2

**Roxygen** list(old\_usage = TRUE)

**URL** <https://receptiviti.github.io/receptiviti-r/>,  
<https://github.com/Receptiviti/receptiviti-r>

**BugReports** <https://github.com/Receptiviti/receptiviti-r/issues>

**Encoding** UTF-8

**Repository** <https://receptiviti.r-universe.dev>

**RemoteUrl** <https://github.com/receptiviti/receptiviti-r>

**RemoteRef** HEAD

**RemoteSha** d92bb4f9f391ecf55906982b9e2dd87191306c9f

## Contents

|                               |   |
|-------------------------------|---|
| receptiviti . . . . .         | 2 |
| receptiviti_norming . . . . . | 6 |

|              |          |
|--------------|----------|
| <b>Index</b> | <b>8</b> |
|--------------|----------|

receptiviti

*Receptiviti API***Description**

The main function to access the **Receptiviti** API.

**Usage**

```
receptiviti(text = NULL, output = NULL, id = NULL, text_column = NULL,
  id_column = NULL, files = NULL, dir = NULL, file_type = "txt",
  encoding = NULL, return_text = FALSE,
  api_args = getOption("receptiviti.api_args", list()),
  frameworks = getOption("receptiviti.frameworks", "all"),
  framework_prefix = TRUE, as_list = FALSE, bundle_size = 1000,
  bundle_byte_limit = 7500000, collapse_lines = FALSE, retry_limit = 50,
  clear_cache = FALSE, clear_scratch_cache = TRUE, request_cache = TRUE,
  cores = detectCores() - 1, use_future = FALSE, in_memory = TRUE,
  verbose = FALSE, overwrite = FALSE, compress = FALSE,
  make_request = TRUE, text_as_paths = FALSE,
  cache = Sys.getenv("RECEPTIVITI_CACHE"), cache_overwrite = FALSE,
  cache_format = Sys.getenv("RECEPTIVITI_CACHE_FORMAT", "parquet"),
  key = Sys.getenv("RECEPTIVITI_KEY"),
  secret = Sys.getenv("RECEPTIVITI_SECRET"),
  url = Sys.getenv("RECEPTIVITI_URL"),
  version = Sys.getenv("RECEPTIVITI_VERSION"),
  endpoint = Sys.getenv("RECEPTIVITI_ENDPOINT"))
```

```
receptiviti_status(url = Sys.getenv("RECEPTIVITI_URL"),
  key = Sys.getenv("RECEPTIVITI_KEY"),
  secret = Sys.getenv("RECEPTIVITI_SECRET"), verbose = TRUE,
  include_headers = FALSE)
```

**Arguments**

|                        |   |
|------------------------|---|
| text                   | A character vector with text to be processed, path to a directory containing files, or a vector of file paths. If a single path to a directory, each file is collapsed to a single text. If a path to a file or files, each line or row is treated as a separate text, unless <code>collapse_lines</code> is TRUE (in which case, files will be read in as part of bundles at processing time, as is always the case when a directory). Use files to more reliably enter files, or <code>dir</code> to more reliably specify a directory. |
| output                 | Path to a <code>.csv</code> file to write results to. If this already exists, set <code>overwrite</code> to TRUE to overwrite it.   |
| id                     | Vector of unique IDs the same length as <code>text</code> , to be included in the results.  |
| text_column, id_column | Column name of text/id, if <code>text</code> is a matrix-like object, or a path to a csv file.  |

|                                  |  |
|----------------------------------|--|
| <code>files</code>               | A list of file paths, as alternate entry to <code>text</code> .  |
| <code>dir</code>                 | A directory to search for files in, as alternate entry to <code>text</code> .  |
| <code>file_type</code>           | File extension to search for, if <code>text</code> is the path to a directory containing files to be read in.  |
| <code>encoding</code>            | Encoding of file(s) to be read in. If not specified, this will be detected, which can fail, resulting in mis-encoded characters; for best (and fastest) results, specify encoding.   |
| <code>return_text</code>         | Logical; if TRUE, <code>text</code> is included as the first column of the result.   |
| <code>api_args</code>            | A list of additional arguments to pass to the API (e.g., <code>list(sallee_mode = "sparse")</code> ). Defaults to the <code>receptiviti.api_args</code> option.  |
| <code>frameworks</code>          | A vector of frameworks to include results from. Texts are always scored with all available framework – this just specifies what to return. Defaults to all, to return all scored frameworks. Can be set by the <code>receptiviti.frameworks</code> option (e.g., <code>options(receptiviti.frameworks = c("liwc", "sallee"))</code> ). |
| <code>framework_prefix</code>    | Logical; if FALSE, will remove the framework prefix from column names, which may result in duplicates. If this is not specified, and 1 framework is selected, or <code>as_list</code> is TRUE, will default to remove prefixes.  |
| <code>as_list</code>             | Logical; if TRUE, returns a list with frameworks in separate entries.  |
| <code>bundle_size</code>         | Number of texts to include in each request; between 1 and 1,000.   |
| <code>bundle_byte_limit</code>   | Memory limit (in bytes) of each bundle, under 1e7 (10 MB, which is the API's limit). May need to be lower than the API's limit, depending on the system's requesting library.  |
| <code>collapse_lines</code>      | Logical; if TRUE, and <code>text</code> contains paths to files, each file is treated as a single text.  |
| <code>retry_limit</code>         | Maximum number of times each request can be retried after hitting a rate limit.  |
| <code>clear_cache</code>         | Logical; if TRUE, will clear any existing files in the cache. Use <code>cache_overwrite</code> if you want fresh results without clearing or disabling the cache. Use <code>cache = FALSE</code> to disable the cache.   |
| <code>clear_scratch_cache</code> | Logical; if FALSE, will preserve the bundles written when <code>in_memory</code> is TRUE, after the request has been made.   |
| <code>request_cache</code>       | Logical; if FALSE, will always make a fresh request, rather than using the response from a previous identical request.   |
| <code>cores</code>               | Number of CPU cores to split bundles across, if there are multiple bundles. See the Parallelization section.   |
| <code>use_future</code>          | Logical; if TRUE, uses a future back-end to process bundles, in which case, parallelization can be controlled with the <code>plan</code> function (e.g., <code>plan("multisession")</code> to use multiple cores); this is required to see progress bars when using multiple cores. See the Parallelization section.                   |
| <code>in_memory</code>           | Logical; if FALSE, will write bundles to temporary files, and only load them as they are being requested.  |

|                              |   |
|------------------------------|---|
| <code>verbose</code>         | Logical; if TRUE, will show status messages.  |
| <code>overwrite</code>       | Logical; if TRUE, will overwrite an existing output file.   |
| <code>compress</code>        | Logical; if TRUE, will save as an xz-compressed file.   |
| <code>make_request</code>    | Logical; if FALSE, a request is not made. This could be useful if you want to be sure and load from one of the caches, but aren't sure that all results exist there; it will error out if it encounters texts it has no other source for. |
| <code>text_as_paths</code>   | Logical; if TRUE, ensures text is treated as a vector of file paths. Otherwise, this will be determined if there are no NAs in text and every entry is under 500 characters long.   |
| <code>cache</code>           | Path to a directory in which to save unique results for reuse; defaults to <code>Sys.getenv("RECEPTIVITI_CACHE")</code> . See the Cache section for details.  |
| <code>cache_overwrite</code> | Logical; if TRUE, will write results to the cache without reading from it. This could be used if you want fresh results to be cached without clearing the cache.  |
| <code>cache_format</code>    | Format of the cache database; see <a href="#">FileFormat</a> . Defaults to <code>Sys.getenv("RECEPTIVITI_CACHE_FORMAT")</code> .  |
| <code>key</code>             | API Key; defaults to <code>Sys.getenv("RECEPTIVITI_KEY")</code> .   |
| <code>secret</code>          | API Secret; defaults to <code>Sys.getenv("RECEPTIVITI_SECRET")</code> .   |
| <code>url</code>             | API URL; defaults to <code>Sys.getenv("RECEPTIVITI_URL")</code> , which defaults to <code>"https://api.receptiviti.com/"</code> .   |
| <code>version</code>         | API version; defaults to <code>Sys.getenv("RECEPTIVITI_VERSION")</code> , which defaults to <code>"v1"</code> .   |
| <code>endpoint</code>        | API endpoint (path name after the version); defaults to <code>Sys.getenv("RECEPTIVITI_ENDPOINT")</code> , which defaults to <code>"framework"</code> .  |
| <code>include_headers</code> | Logical; if TRUE, <code>receptiviti_status</code> 's verbose message will include the HTTP headers.   |

## Value

A `data.frame` with columns for text (if `return_text` is TRUE; the originally entered text), `id` (if one was provided), `text_hash` (the MD5 hash of the text), a column each for relevant entries in `api_args`, and scores from each included framework (e.g., `summary.word_count` and `liwc.i`). If `as_list` is TRUE, returns a list with a named entry containing such a `data.frame` for each framework.

## Cache

If the `cache` argument is specified, results for unique texts are saved in an [Arrow](#) database in the `cache` location (`Sys.getenv("RECEPTIVITI_CACHE")`), and are retrieved with subsequent requests. This ensures that the exact same texts are not re-sent to the API. This does, however, add some processing time and disc space usage.

If `cache` is TRUE, a default directory (`receptiviti_cache`) will be looked for in the system's temporary directory (which is usually the parent of `tempdir()`). If this does not exist, you will be asked if it should be created.

The primary cache is checked when each bundle is processed, and existing results are loaded at that time. When processing many bundles in parallel, and many results have been cached, this can cause the system to freeze and potentially crash. To avoid this, limit the number of cores, or disable parallel processing.

The `cache_format` arguments (or the `RECEPTIVITI_CACHE_FORMAT` environment variable) can be used to adjust the format of the cache.

You can use the cache independently with `open_database(Sys.getenv("RECEPTIVITI_CACHE"))`.

You can also set the `clear_cache` argument to `TRUE` to clear the cache before it is used again, which may be useful if the cache has gotten big, or you know new results will be returned. Even if a cached result exists, it will be reprocessed if it does not have all of the variables of new results, but this depends on there being at least 1 uncached result. If, for instance, you add a framework to your account and want to reprocess a previously processed set of texts, you would need to first clear the cache.

Either way, duplicated texts within the same call will only be sent once.

The `request_cache` argument controls a more temporary cache of each bundle request. This is cleared when the R session ends. You might want to set this to `FALSE` if a new framework becomes available on your account and you want to process a set of text you already processed in the current R session without restarting.

Another temporary cache is made when `in_memory` is `FALSE`, which is the default when processing in parallel (when `cores` is over 1 or `use_future` is `TRUE`). This contains a file for each unique bundle, which is read in as needed by the parallel workers.

## Parallelization

texts are split into bundles based on the `bundle_size` argument. Each bundle represents a single request to the API, which is why they are limited to 1000 texts and a total size of 10 MB. When there is more than one bundle and either `cores` is greater than 1 or `use_future` is `TRUE` (and you've externally specified a [plan](#)), bundles are processed by multiple cores.

If you have texts spread across multiple files, they can be most efficiently processed in parallel if each file contains a single text (potentially collapsed from multiple lines). If files contain multiple texts (i.e., `collapse_lines = FALSE`), then texts need to be read in before bundling in order to ensure bundles are under the length limit.

Whether processing in serial or parallel, progress bars can be specified externally with [handlers](#); see examples.

## Examples

```
## Not run:

# check that the API is available, and your credentials work
receptiviti_status()

# score a single text
single <- receptiviti("a text to score")

# score multiple texts, and write results to a file
multi <- receptiviti(c("first text to score", "second text"), "filename.csv")
```

```

# score many texts in separate files
## defaults to look for .txt files
file_results <- receptiviti(dir = "./path/to/txt_folder")

## could be .csv
file_results <- receptiviti(
  dir = "./path/to/csv_folder",
  text_column = "text", file_type = "csv"
)

# score many texts from a file, with a progress bar
## set up cores and progress bar (only necessary if you want the progress bar)
future::plan("multisession")
progressr::handlers(global = TRUE)
progressr::handlers("progress")

## make request
results <- receptiviti(
  "./path/to/largefile.csv",
  text_column = "text", use_future = TRUE
)

## End(Not run)

```

---

receptiviti\_norming      *View or Establish Custom Norming Contexts*

---

## Description

View or Establish Custom Norming Contexts

## Usage

```

receptiviti_norming(name = NULL, text = NULL, options = list(),
  id = NULL, text_column = NULL, id_column = NULL, files = NULL,
  dir = NULL, file_type = "txt", collapse_lines = FALSE,
  encoding = NULL, bundle_size = 1000, bundle_byte_limit = 7500000,
  retry_limit = 50, clear_scratch_cache = TRUE, cores = detectCores() -
  1, use_future = FALSE, in_memory = TRUE,
  url = Sys.getenv("RECEPTIVITI_URL"), key = Sys.getenv("RECEPTIVITI_KEY"),
  secret = Sys.getenv("RECEPTIVITI_SECRET"), verbose = TRUE)

```

## Arguments

|      |  |
|------|--|
| name | Name of a new norming context, to be established from the provided text. Not providing a name will list the previously created contexts. |
| text | Text to be processed and used as the custom norming context. Not providing text will return the status of the named norming context.     |

options Options to set for the norming context (e.g., `list(word_count_filter = 350, punctuation_filter = .25)`).

id, text\_column, id\_column, files, dir, file\_type, collapse\_lines, encoding Additional arguments used to handle text; same as those in [receptiviti](#).

bundle\_size, bundle\_byte\_limit, retry\_limit, clear\_scratch\_cache, cores, use\_future, in\_memory Additional arguments used to manage the requests; same as those in [receptiviti](#).

key, secret, url Request arguments; same as those in [receptiviti](#).

verbose Logical; if TRUE, will show status messages.

### Value

If name is not specified, a data.frame containing the statuses of each available custom norming context. If text is not specified, the status of the named context in a list. If texts are provided, a list:

- `initial_status`: Initial status of the context.
- `first_pass`: Response after texts are sent the first time, or NULL if the initial status is `pass_two`.
- `second_pass`: Response after texts are sent the second time.

### Examples

```
## Not run:
# get status of all existing custom norming contexts
contexts <- receptiviti_norming()

# create or get the status of a single custom norming context
status <- receptiviti_norming("new_context")

# establish a new custom norming context
full_status <- receptiviti_norming("new_context", c(
  "a text to set the norm",
  "another text part of the new context"
))

## End(Not run)
```

# Index

FileFormat, [4](#)

handlers, [5](#)

plan, [3](#), [5](#)

receptiviti, [2](#), [7](#)

receptiviti\_norming, [6](#)

receptiviti\_status (receptiviti), [2](#)